



# INMOTION Controls, Inc.

532 Series Radio / Remote Control



INMOTION Controls' 532 Series Radios / Remote Control is a versatile System, ideal for complex industrial applications. The compact Transmitter fits easily in the users hand and has the same added safety features that make all of INMOTION CONTROLS products so popular. The 532 Series is a 3 – motion, 2 – speed, radio suitable for most industrial applications using Variable Frequency Drives or stepped contactor control. The 532 Series offers options for a built-in horn and A / BOTH / B functionality. With a range of 300 feet, the 532 can operate in many environments without compromising safety. As with all INMOTION CONTROLS products, the 532 comes with a one year warranty against manufactures' defects.

**WE HAVE OTHER MODELS AVAILABLE  
FOR ANY APPLICATION**

# INMOTION Controls, Inc.

## Available Configurations

- 532 SYSTEM – 3 motion, 2 speed
- 532-H SYSTEM – 3 motion, 2 speed with built-in horn
- 532-A/B SYSTEM – 3 motion, 2 speed with A/BOTH/B
- 532-A/B-H SYSTEM – 3 motion, 2 speed with A/BOTH/B and horn

## General Specifications

- Two Transmitters and one Receiver included
- Enclosure: Fiberglass
- Environment: IP 65 (indoor/outdoor)
- Frequency: 310 – 331 MHz (crystal based)
- Operating Temperature: -49° F to 176° F
- ID Code: 32 bit
- Range: 300 feet

## Transmitter

- Sealed START power button
- Changeable button labels
- Shock-resistant design
- Optional protective boot
- Two stage power indicator
- Minimal power consumption (40mA)

## Receiver

- Alarm and signal light output
- Optional built-in horn
- Vibration resistant
- Enhanced watchdog circuit
- Source and output fused relays
- 110 VAC (standard operating)
- Optional 24, 48 or 220 VAC
- Optional 12-24 DC

