

ECONOMICAL DEPENDABLE SAFE

With a Rebel Self Retracting Lifeline (SRL), you get an economical fall protection solution that won't compromise the safety or performance of your crew. Rebel continues to set performance standards beyond compliance, while providing a substantial value compared to competitive models.

- Improved Shock Pack Design (6' - 20' Units)
- Rugged, Lightweight Housing
- Recessed Labels To Increase Product Life
- Impact Indicator
- Swiveling Anchorage
- 3,600 Lb. Gate Capacity
- 420 Lb. Models Available (33' units and above)



3100432
REBEL 20 Ft. (6.1 m) SRL

20 ft. (6.1 m) of 1" (2.5 cm) polyester web with steel swiveling snap hook, swiveling anchorage and carabiner.



3590019
REBEL 15 Ft. (4.5 m) SRL

15 ft. (4.5 m) of 3/16" (5 mm) galvanized steel wire rope with steel swiveling snap hook, swiveling anchorage and carabiner.



3100425
REBEL 11 Ft. (3.3 m) SRL

11 ft. (3.3 m) of 1" (2.5 cm) polyester web with steel snap hook, swiveling anchorage and carabiner.



DOZENS OF WAYS TO STAY COMPLIANT WITHOUT COMPROMISE

| Lifeline Material | Web/Cable Length | | | | | | | | | |
|----------------------------------|------------------|----------------|----------------|-----------------|-------------------|-------------------|----------------|------------------|--------------------|--|
| | 6' (1.8 m) | 11' (3.3 m) | 15' (4.5 m) | 20' (6 m) | 33' (10 m) | 50' (15 m) | 66' (20 m) | 85' (26 m) | 100' (30 m) | |
| Thermoplastic Housing | | | | | | | | | | |
| Aluminum Housing | | | | | | | | | | |
| Stackable | | | | | | | | | | |
| Impact Indicator | | | | | | | | | | |
| Swiveling Anchorage | | | | | | | | | | |
| Self Locking Snap Hook | | | | | | | | | | |
| Rebar Hook | | | | | | | | | | |
| Swiveling Hook | | | | | | | | | | |
| Leading Edge | | | | | | | | | | |
| 100% Tie-Off | | | | | | | | | | |
| 310 lb. (140 kg) Weight Capacity | | | | | | | | | | |
| 420 lb. (190 kg) Weight Capacity | | | | | | | | | | |
| Galv Cable | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| SS Cable | | | | | | | | | | |
| | | | | | | | | | | |
| Web | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| Weight | Varies | Varies | Varies | Varies | 13.5 lb. (6.1 kg) | 17.3 lb. (7.8 kg) | 22 lb. (10 kg) | 28.6 lb. (13 kg) | 29.5 lb. (13.4 kg) | |
| Approximate depth | 2" (5 cm) | 3" (8 cm) | 3" (8 cm) | 4.6" (12 cm) | 4.6" (12 cm) | 4.6" (12 cm) | 5.5" (14 cm) | 5.5" (14 cm) | 5.5" (14 cm) | |
| Approximate width | 3.5" (8.9 cm) | 6" (15 cm) | 6" (15 cm) | 9.8" (24.9 cm) | 9.8" (24.9 cm) | 11" (28 cm) | 12.8" (33 cm) | 12.8" (33 cm) | 12.8" (33 cm) | |
| Approximate height* | 19" (48 cm) | 19" (48 cm) | 29" (74 cm) | 22.5" (57.1 cm) | 22.5" (57.1 cm) | 23.8" (61 cm) | 25.7" (65 cm) | 25.7" (65 cm) | 25.7" (65 cm) | |

*Anchor point to anchor point

Standards: Meets OSHA 1926.502, OSHA 1910.66, ANSI Z359.1, ANSI Z359.12, ANSI A10.32, CSA Z259.2.2 Type II



Capital Safety
 USA: 800 328 6146
www.capitalsafety.com info@capitalsafety.com

[@Capital_Safety](https://twitter.com/Capital_Safety) [Facebook.com/CapitalSafety](https://www.facebook.com/CapitalSafety)

FOR MORE INFORMATION VISIT US AT CAPITALSAFETY.COM